

COPPER IMPREGNATED SQUARES

Tolerance: +.030/-0.000" (Surfaced)

Technical Specifications

| Grade | Color Identification | Shore Hardness | Flexural Strength (PSI) | Resistance (0.000 ohm/in.) | Particle Size (microns) |
|---------------|----------------------|----------------|-------------------------|----------------------------|-------------------------|
| POCO EDM-C200 | Green / White Stripe | 62 | 12,100 | 114 | 10 |
| POCO EDM-C3 | Orange | 66 | 20,300 | 127 | <5 |
| TTK-4C | Yellow | 60 | 15,500 | 100 | 4 |



*Copper Impregnated Graphite – [Learn More](#)

Order any custom size or tolerance

| Size (Inch) | | Catalog No. | | |
|-------------|--------|---------------|-------------|--------|
| Thickness | Length | POCO EDM-C200 | POCO EDM-C3 | TTK-4C |
| 1/4 | 6 | G24008 | GY4008 | GC4008 |
| 1/4 | 12 | G24012 | GY4012 | GC4012 |
| 3/8 | 6 | G24016 | GY4016 | GC4016 |
| 3/8 | 12 | G24020 | GY4020 | GC4020 |
| 1/2 | 6 | G24028 | GY4028 | GC4028 |
| 1/2 | 12 | G24032 | GY4032 | GC4032 |
| 3/4 | 6 | G24040 | GY4040 | GC4040 |
| 3/4 | 12 | G24044 | GY4044 | GC4044 |
| 1 | 6 | G24052 | GY4052 | GC4052 |
| 1 | 12 | G24056 | GY4056 | GC4056 |
| 1-1/2 | 6 | G24060 | GY4060 | GC4060 |
| 1-1/2 | 12 | G24064 | GY4064 | GC4064 |
| 2 | 6 | G24072 | GY4072 | GC4072 |
| 2 | 12 | G24076 | GY4076 | GC4076 |