

Safety Data Sheet acc. to OSHA HCS

Printing date 10/31/2018 Version 8 Reviewed on 10/31/2018

1 Identification

· Product identifier

EcoSpark 105 · Product name:

A100501 · Product code: · Former product code (till July 2012): 50034

· Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the

mixture Industrial use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: oelheld GmbH

> Ulmer Str. 133-139 70188 Stuttgart GERMANY

Tel.: +49-(0)711-16863-0 Fax.: +49-(0)711-16863-3500 E-Mail: hutec@oelheld.de Internet: www.oelheld.de oelheld U.S., Inc.

· Imported by: 1100 Wesemann Drive

West Dundee, Illinois (US) - 60118

Phone: +1-847-531-8501 Email: hutec-us@oelheld.com

FAX: +1-847-531-8511 www.oelheld.com

· Information department: Tel. +49-(0)711-16863-0

msds@oelheld.de

· Emergency telephone number: In the event of a medical or chemical emergency contact ChemTel Inc.™

North America 1-800-255-3924 or Worldwide Intl. +1-813-248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

GHS08

Danger

· Signal word · Hazard-determining components of

labeling:

Distillates (petroleum) hydrotreated light, C9-C16 Distillates (petroleum), hydrotreated middle

· Hazard statements H304 May be fatal if swallowed and enters airways. · Precautionary statements P280 Wear protective gloves.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)

Health = 1 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = 1 Fire = 1REACTIVITY | Reactivity = 0

· Other hazards

The NFPA- and the HMIS-ratings range from 0 (least severe hazard) to 4 (most severe

hazard).

NFPA and HMIS are regulations in the USA.

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/31/2018 Version 8 Reviewed on 10/31/2018

Product name: EcoSpark 105

(Contd. of page 1)

NFPA: National Fire Protection Association HMIS: Hazardous Material Identification System

Personal protective equipment (PPE) Codes: We recommend the following personal

protection:

. HMIS Letter B - Required Equipment: Safety glasses, gloves

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

64742-47-8 Distillates (petroleum) hydrotreated light, C9-C16 50-100% Asp. Tox. 1, H304 64742-46-7 Distillates (petroleum), hydrotreated middle 2.5-10% Asp. Tox. 1, H304

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information: Remove any clothing soiled by the product.

In case of occuring of symptoms or in doubt consult a doctor. If a doctor is consulted show this material safety data sheet. Supply fresh air; consult doctor in case of complaints.

· After inhalation: · After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor.

· After ingestion: Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed · Indication of any immediate medical

No further relevant information available.

attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

Suitable extinguishing media:

· For safety reasons unsuitable extinguishing media:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Water with full jet

· Special hazards arising from the substance or mixture

In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

· Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device. Cool endangered receptacles with water spray. · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency

procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product. · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil. Keep contaminated washing water and dispose of appropriately.

· Methods and material for

containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13. Remove from the water surface (e.g. skim or suck off).

· Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

None of the ingredients is listed.

(Contd. on page 3)



Safety Data Sheet acc. to OSHA HCS

Product name: EcoSpark 105

(Contd. of page 2)

· PAC-2:

None of the ingredients is listed.

· PAC-3:

None of the ingredients is listed.

7 Handling and storage

· Handling:

• Precautions for safe handling Ensure good ventilation/exhaust at the workplace.

Not required.

Open and handle receptacle with care.

Recommendation: Level of dielectric over the place of erosion min. 50 mm.

· Information about protection against

explosions and fires: Fumes can combine with air to form an explosive mixture above the flash point.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

· Information about storage in one

common storage facility:

Further information about storage

conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat, direct sunlight and UV-rays.

Storage stability under the described conditions: 24 months.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design

of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

64742-46-7 Distillates (petroleum), hydrotreated middle

OSHA (PEL) OIL MISTS (USA) Long-term value: 5 mg/m³

· Exposure controls

Personal protective equipment:

· General protective and hygienic

measures: The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the skin.

Wash hands before breaks and at the end of work.

• Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation or in cases

where overexposures may occur.

Protection of hands:Material of glovesProtective glovesNitrile rubber, NBR

Penetration time of glove material At a glove thickness of about 0,4 mm the value of the permeation breakthrough in

accordance with EN 374 is for chemically similar products according to the manufacturer:

>480 min. (Degradation EN 374 rating class 6)

These statements are based on laboratory test methods which could not simulate working conditions exactly. The responsibility rests with the end user for choosing the right gloves

for his application.

Eye protection: Goggles recommended during refilling.

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Color: Colorless
Odor: Characteristic
Odor threshold: Not determined.

pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Product name: EcoSpark 105

(Contd. of page 3)

Boiling point/Boiling range: > 235 °C (>455 °F)

· Flash point: 105 °C (221 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: Not determined.

· Decomposition temperature: Not determined.

• Danger of explosion: Product is not explosive. However formation of explosive air/vapour mixtures above the

flash point or in case of strong misting is possible.

· Explosion limits:

Lower: 0.5 Vol % 0.5 Vol % 6.5 Vol %
• Vapor pressure: Not determined.

• Density at 15 °C (59 °F): 0.815 g/cm³ (6.801 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Kinematic at 40 °C (104 °F): 2.3 mm²/s

· Solvent content:

VOC (EC) None VOC (California) None

· Oxidising properties: Not determined.

Other information
 No further relevant information available.

· Additional information The data of the explosion limits are based on the base oil.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· Chemical stability

 $\cdot \ \, \text{Thermal decomposition} \ / \ \, \text{conditions}$

to be avoided: No decomposition if used according to specifications.

• Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid See above

· Incompatible materials: Strong oxidizing agents

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for

classification:

ATE mix:
Oral: Acute toxicity estimate: > 2,000 mg/kg
Dermal: Acute toxicity estimate: > 2,000 mg/kg

Inhalation: Acute toxicity estimate: for gases > 20,000 ppmV; for vapours > 20 mg/l; for

dust/mist > 5 mg/l

64742-47-8 Distillates (petroleum) hydrotreated light, C9-C16

Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50 / 4h >4,951 mg/m³ (rat)

· Primary irritant effect:

on the skin: Repeated/long exposure may cause skin dryness and in consequence skin irritations.

on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 5)



Safety Data Sheet acc. to OSHA HCS

 Printing date 10/31/2018
 Version 8
 Reviewed on 10/31/2018

Product name: EcoSpark 105

(Contd. of page 4)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

64742-47-8 Distillates (petroleum) hydrotreated light, C9-C16

EL0 / 48h | 1,000 mg/l (Daphnia magna)

EL0 / 72h 1,000 mg/l (Pseudokirchneriella subcapitata)

Persistence and degradability

Easily biodegradable

· Behavior in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

Ecotoxical effects:

· Behavior in sewage processing

plants:
Other adverse effects

The product can be mechanically separated. No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation: Delivery of waste oil to offically authorized collectors only.

· Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

· DOT, ADN, IMDG, IATA

· Class Void

· ADR

· Class Void · Label Void

· Packing group

· DOT, ADR, IMDG, IATA Void

· Environmental hazards: Not applicable.

· Marine pollutant:

Special precautions for user
 Not applicable.

· Transport in bulk according to Annex II of MARPOL73/78

and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· ADR

Excepted quantities (EQ):
Limited quantities (LQ)
Transport category
Tunnel restriction code

Void
Void

IMDG

· Limited quantities (LQ) Void · Excepted quantities (EQ) Void

· IATA

· Remarks: Void.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/31/2018 Version 8 Reviewed on 10/31/2018

Void

Product name: EcoSpark 105

(Contd. of page 5)

· UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- **Proposition 65**
- Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

See section 8 for information.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for alterations General revision.

· Relevant phrases H304 May be fatal if swallowed and enters airways.

· Department issuing SDS: Department of Research & Development

Date of preparation / last revision

10/31/2018 / 7

· Abbreviations and acronyms:

EC: European Community CAS: Chemical Abstracts Service (division of the American Chemical Society)

ACGIH: American Conference of Governmental Industrial Hygienists OEL: Occupational Exposure Limit

PNOS: Particles Not Otherwise Specified STEL: Short Time Exposure Limit TLV: Threshold Limit Value

TWA: Time Weighted Average concentration WEEL: Workplace Environmental Exposure Level

TLV: Threshold limit value
TWA: Time Weighted Average concentration
STEL: Short Time Exposure Limit
IOELV: Indicative Occupational Exposure Limit Value

OSHA: Occupational Safety & Health Administration of the U.S. Departement of Labor

ACGIH: American Conference of Governmental Industrial Hygienists GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EC50: ecotoxic concentration, 50 percent NOEC: no observed effect concentrations

NOELR: No observed effect loading rate OECD: the Organisation for Economic Co-operation and Development [coordinates the OECD guidelines for the

toxicological testing of chemicals]
ATE: acute toxicity estimate
NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health
VOC: Volatile Organic Compounds (USA, EC)
ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association Asp. Tox. 1: Aspiration hazard - Category

· * Data compared to the previous version altered

US-