

MICROGRAPH GRAPHITE SQUARES

Tolerance: +.030/-0.000" (Surfaced)

Technical Specifications

Grade	Color Identification	Shore Hardness	Flexural Strength (PSI)	Resistance (0.000 ohm*in)	Particle Size (microns)
MG-4	Pink	55	9,240	500	12
MG-5	Brown	63	7,540	528	8
MG-8	Blue/Yellow	76	9,458	591	5
MG-9	Gold / Red	68	11,603	630	5
TTK-4	Silver	72	10,600	552	4
TTK-4C	Orange / White	60	15,500	100	4



*Carbon Based Graphite

*Copper Impregnated Graphite – [Learn More](#)



TOYO TANSO
Inspiration for Innovation



Order any custom
size or tolerance

Size (Inch)		Catalog No.					
Thickness	Length	MG-4	MG-5	MG-8	MG-9	TTK-4	TTK-4C
1/4	6	GH4008	GJ4008	GQ4008	GF4008	GL4008	GC4008
1/4	12	GH4012	GJ4012	GQ4012	GF4012	GL4012	GC4012
3/8	6	GH4016	GJ4016	GQ4016	GF4016	GL4016	GC4016
3/8	12	GH4020	GJ4020	GQ4020	GF4020	GL4020	GC4020
1/2	6	GH4028	GJ4028	GQ4028	GF4028	GL4028	GC4028
1/2	12	GH4032	GJ4032	GQ4032	GF4032	GL4032	GC4032
5/8	12	GH4036	GJ4036	GQ4036	GF4036	GL4036	GC4036
3/4	6	GH4040	GJ4040	GQ4040	GF4040	GL4040	GC4040
3/4	12	GH4044	GJ4044	GQ4044	GF4044	GL4044	GC4044
1	6	GH4052	GJ4052	GQ4052	GF4052	GL4052	GC4052
1	12	GH4056	GJ4056	GQ4056	GF4056	GL4056	GC4056
1-1/2	12	GH4064	GJ4064	GQ4064	GF4064	GL4064	GC4064
2	12	GH4076	GJ4076	GQ4076	GF4076	GL4076	GC4076