



















FA(ALL)-MD PRO CONSUMABLES

| ITEM | IMAGE | DESCRIPTION | PART NO. <small>FA / FA-V</small> | PART NO. <small>FA-P / FA-PS / FA-VS / FA-S</small> | QTY REQUIRED |
|--------------------------|---|--|--------------------------------------|--|--------------|
| DIAMOND GUIDE (UPPER) |  | .008" (0.2mm) Upper Diamond Guide | A600 | A620 | 1 |
| | | D.D. GUIDE 0.2MM (A) UPPER FA30 COLUMN UP | A606 | - | 1 |
| | | .010" (0.25mm) Upper Diamond Guide | A601 | A621 | 1 |
| | | D.D. GUIDE 0.25MM (A) UPPER FA30 COLUMN UP | A607 | - | 1 |
| | | D.D. GUIDE 0.3MM (A) UPPER FA30 COLUMN UP | A608 | - | 1 |
| | | D.D. GUIDE 0.36MM FAVS UPPER | DAL1800 | | 1 |
| DIAMOND GUIDE (LOWER) |  | .008" (0.2mm) Lower Diamond Guide | A603 | A623 | 1 |
| | | .010" (0.25mm) Lower Diamond Guide | A604 | A624 | 1 |
| | | .012" (0.3mm) Lower Diamond Guide | A605 | A625 | 1 |
| | | D.D. GUIDE 0.36MM FAVS LOWER | DAM3400 | | 1 |

| ITEM | IMAGE | DESCRIPTION | PART NO. | QTY REQUIRED |
|-------------------------|---|---|---------------|--------------|
| FILTERS |  | OEM Van-TG High Performance Premium Filter | VFC169J | 2 |
| |  | CPG High Performance Filter | CPG169B | 2 |
| |  | 3-5 MICRON MIT/MAK/FAN FA ADV/BA/NA/MD/SP/EU/IC/ID/IB | CPG1312-FMKIT | 2 |
| | | 3-5 MICRON FOR CX/FX/FA/QA/RA | CPG1312-QC | 2 |
| CARBIDES/ POWERFEEDS |  | VAN-TG POWER FEEDER EXT.D. LIFE | VPFC632-3 | 1 |
| | | POWER FEEDER AF2 | S632 | 1 |
| | | UNPOLISHED POWER FEEDER | S632UP | 1 |
| | | FA-V Power Feeder | DQ20600 | 1 |
| FLUSH CUPS |  | UPPER FLUSH CUP 4MM AF2/AF3/AT FOR CX AF MACHINES | DQ44200 | 1 |
| | | UPPER FLUSH NOZZLE 8MM FOR AT, AF3, AF2 | DQ44300 | 1 |
| |  | FLUSHING NOZZLE (DWN) 4.0mm Replacing S606 | DQ30300 | 1 |
| | | FLUSHING NOZZLE (DWN) 4.0mm | VFC606 | 1 |
| | | FLUSHING NOZZLE (DWN) 8.0MM [OEM] | DQ30400 | 1 |
| | | FLUSHING NOZZLE (DWN) 8.0MM [AFTERMARKET] | VFC633 | 1 |
| RESIN |  | Regeneration Coupon for 1/2 Cubic Foot Resin Sock | A403A | 1 |
| | | Regeneration Coupon for 1.4 Cubic Foot Resin Tank | A448A | 1 |
| RESIN PRE-FILTERS |  | 1 MICRON PRE FILTER | A405A1 | 1 |
| | | 5 MICRON PREFILTER CTRG 8BIG5MI | A405 | 1 |
| | | 20 MICRON PREFILTER | A429 | 1 |



| ITEM | IMAGE | DESCRIPTION | PART NO. | QTY REQUIRED |
|---------------------|---|---|-------------------------------------|--------------|
| FLUIDS |  | CPG-CLEAN 1 GALLON CONTAINER | CPG-CLEAN-1G | 1 |
| |  | CLC CORROSION INHIBITOR 1 GALLON CONTAINER | Enviro-CI | 1 |
| |  | VAN-TG ULTRASONIC CLEANER KIT | VUC001 | 1 |
| | | WATER SOLUBLE ALKALINE CLEANER 16 OZ BOTTLE FOR CLEANER KIT | A168-Z16 | 1 |
| WIRE PROCESSOR |  | Wire Chopper with Fixed Blade | DDV7400 | 1 |
| | | Extended life Chopper | DC-M1535-EXT.3 | 1 |
| |  | FIXED BLADE FA | DAY6100 | 1 |
| RECOMMENDED WIRE(S) |  | Van-TG Premium Non Paraffin Wire (148,000 psi) | CONTACT CPG 888-297-9895 | |
| | | Van-TG Standard Wire | | |
| | | CPG-ZT Hybrid | | |
| | | CPG-Xpress Zinc Coated Wire | | |

