Trust DS4 Ultra-fine EDM Graphite for your Toughest Jobs

Ŷ

"The intricate EDM electrodes required to produce our audio speaker grills take 7+ days of machining and 30+ hours of EDM burning. We needed a graphite we can trust to withstand this demanding application. We switched to Mersen's DS4 ultra-fine EDM graphite a few years ago and it's been the best performing graphite we've used. With the DS4 material we have also seen significant savings per electrode."

Eric Jacobsen Hi-Tech Mold & Engineering





DS4 Delivers:

- Excellent surface finish
- Intricate detail
- Easy to machine
- Exceptionally strong
- Saves significant money

Ask your EDM distributor for DS4H



edm.mersen.com

MERSEN

Industry's Most Complete Line of EDM Graphite from Roughing to High-End Finishing

| Graphite Grade | Density | | Hardness | Flexural Strength | | Electrical Resistivity | | Average Grain Size | |
|--|--------------------------------|------|----------|-------------------------|-----|---------------------------|---------------------------|-----------------------|-----|
| | lbs/ cubic ft | g/cc | Shore | psi | MPa | Ω inch | $\mu \Omega \mathrm{cm}$ | inch | μ m |
| ELLOR® DS4 DARKSTER Ultra fine grain graphite Ultimate precision & EDM performance | 117 | 1.88 | 72 | 13,500 | 93 | .00050 | 1,320 | <0.0002 | 4 |
| ELLOR® DS4C DARKSTOR Ultra fine grain copper impregnated graphite Exceptional EDM performance & precision | 187 | 3.00 | 75 | 19,000 | 131 | .00015 | 381 | <0.0002 | 4 |
| ELLOR [®] +50 High density ultra fine grain graphite Lowest electrode wear | 116 | 1.86 | 80 | 11,000 | 76 | .00054 | 1,370 | 0.0002 | 5 |
| ELLOR [®] +40 Ultra fine grain graphite Lowest electrode wear, fine detail | 111 | 1.78 | 60 | 8,700 | 60 | .00050 | 1,270 | 0.0003 | 7 |
| ELLOR [®] +25 High quality universal graphite Good surface finish | 114 | 1.83 | 65 | 8,000 | 55 | .00048 | 1,220 | 0.0004 | 9 |
| ELLOR [®] +20 Universal graphite Excellent quality & performance ratio | 112 | 1.81 | 65 | 7,500 | 52 | .00049 | 1,240 | 0.0005 | 11 |
| ELLOR [®] +15 Roughing graphite Ideal for high metal removal rate | 111 | 1.78 | 62 | 6,500 | 45 | .00054 | 1,370 | 0.0005 | 12 |
| Distributere | Imont Equipment & Technologiae | | | 2D Craphita & Machining | | | Ohio Corbon Plank Inc | | |

Distributors

Belmont Equipment & Technologies Madison Heights, MI EDM Sales & Supplies, Inc. Maple Grove, MN 3D Graphite & Machining Schaumburg, IL SST Mason, OH Ohio Carbon Blank, Inc. Willoughby, OH Electrodes, Inc. Milford, CT

